



# TECHNICAL DATA SHEET

## GUTTER SEAL+

Gutter Sealing Elastomeric Sealant

---

### PRODUCT DESCRIPTION

Gutter Seal+ is a one-part, high quality blend of synthetic rubber and resin. It exhibits excellent elastomeric properties while maintaining superior adhesion under ponded water conditions.

---

### BASIC USES

Gutter Seal+ has been specifically designed for use in gutter and rainwater applications. It is ideally suited for metal-to-metal and metal-to-plastic joinery, commonly found in and around the eavestrough.

---

### FEATURES & BENEFITS

Gutter Seal+ is easy to apply with conventional caulking equipment and offers excellent elastomeric properties. Gutter Seal+ maintains its superior adhesion capabilities even under ponded water conditions.

Should the Gutter Seal+ be damaged, it can be repaired. Please contact your local Tremco Sales Representative or Tremco Technical Services for repair procedures.

---

### AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 10.1 oz (300 mL) cartridges, packed 30 per case.

---

### COLORS

White

---

### LIMITATIONS

Gutter Seal+ should not be applied to damp or contaminated surfaces. Do not subject Gutter Seal+ to more than 20% movement or expansion.

---

### WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Rheological Properties	ASTM C639	< 3/16" displacement
Hardness Properties	ASTM C661	Shore A hardness 50-60
Tack Free Time	ASTM C679	< 1 hour
Skin Time	ASTM C679	5 minutes
Stain and Color Change	ASTM C510	No staining or color change
Adhesion in Peel	ASTM C794	Dry range to 31 lb. force
Effects of Accelerated Weathering	ASTM C793	No cracks
Adhesion and Cohesion under Cyclic Movement	ASTM C719	25%
Extrusion Rate	ASTM C1183	10-20 mL/min
Effects of Heat Aging	ASTM C1246	5%
Tensile Strength	ASTM D412	350 PSI
Total Elongation	ASTM D412	550%
Percent Solids		70.8%

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

GUTTER-DS/1222

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



[tremcosealants.com](http://tremcosealants.com) | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)