

---

## PRODUCT DESCRIPTION

Willseal® 600S is a pre-compressed, self-expanding foam joint seal, engineered to perform as a highly flexible, secondary seal in vertical applications. Willseal 600S is specifically designed to provide the ideal foundation for a large variety of wet sealants, such as silicone, polyurethane, polysulfide, and acrylic. Unlike conventional wet sealant and backer rod methods, Willseal 600S is not susceptible to breakdowns caused by excessive or rapid joint movements, thus protecting structures against rain, wind, dust, and sound.

---

## BASIC USES

Typically used as an external or interior joint sealant, Willseal 600S can be used as a secondary seal in vertical applications. The following are acceptable applications for Willseal 600S:

- Secondary expansion, control, isolation, and retrofit joints
- Secondary construction joints behind a wet seal
- Joints in pre-cast concrete, masonry, brick, and facades
- Roofing and insulated metal panels
- Exterior insulation finish systems (EIFS)
- Window and flashing applications
- Interior vapor, dust, acoustical, and air control

---

## FEATURES & BENEFITS

Willseal 600S is compatible with a variety of Tremco Sealants and is chemically compatible with many types of commercial construction substrates: will not corrode iron, zinc, steel, galvanized steel, or copper, and will not chemically harm concrete, lightweight concrete, mortar, brick, natural stones, plexiglass, or wood.

- Remains permanently flexible
- Low volatility
- Impregnated with a modified flame retardant
- "Breathable" (vapor permeable)
- Seals gaps or seams as small as 1/8"
- Can be applied in various weather and temperature conditions
- Easy soap-and-water cleanup: no solvents, no cartridges, no pails
- Compatible with most porous or sensitive substrates
- Proven wind driven rain resistance since 1965
- Depth of seal can be changed to increase R-value and sound properties

Willseal 600S is supplied in a pre-compressed state for ease of installation. Material will self-expand to fill the joint. Expansion time will vary based on humidity, temperature, and storage conditions for the prior 24 hours; may differ for wider, thicker material. Material will continue to expand and equalize in the joint.

---

## AVAILABILITY

Available in both rolls and sticks (6.5 ft lengths) from your authorized Tremco distributor, or any Tremco or Willseal Sales Representative. For more information contact Customer Service by phone at 800-274-2813 or email [custserv@willseal.com](mailto:custserv@willseal.com).

- Primary: joint sizes from 1/8" to 2" in rolls
- Joint sizes from 2.25" to 8" in sticks (6.5 ft lengths)
- Custom sizes available upon request

---

## COLORS

Willseal 600S is Black.

---

## LIMITATIONS

Avoid contact of Willseal 600S with hydrocarbon solvents and corrosive chemicals. Willseal 600S cannot be used where standing or ponding water will occur. Not for use in below-grade applications (contact your local Technical Sales Representative for product recommendations).

---

## WARRANTY

A repair or replacement warranty is available on all Willseal products. Visit <https://www.tremcosealants.com/warranties/> for details.

---

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Color		Black
Temperature Stability Range		Short Term: -40 to 248 °F (-40 to 120 °C) Long Term: -40 to 194 °F (-40 to 90 °C)
Ideal Storage Temperature		68 °F (34 °C)
Thermal Conductivity	ASTM C518	0.28 to 0.30 Btu•in/hr•°F•ft <sup>2</sup>
Thermal Resistance	ASTM C518	3.3 to 3.6 hr•°F•ft <sup>2</sup> /Btu
Tensile Strength*	ASTM D3574	21 psi min
Elongation	ASTM D3574	120% ± 20%
Compression Set	ASTM D3574	4.2% max
Staining and Bleeding	DIN 18542	Meets DIN requirements
Resistance to UV and Moisture	DIN 18542	Meets DIN requirements
Comprehensive Performance Test	DIN 18542	600 Pa
Water Penetration:		
Uniform Static	ASTM E331	Pass
Cyclic Static	ASTM E547	Pass
Fire Testing:		
Flame Spread	ASTM E84-12B Class A	5
Smoke Development	ASTM E84-12B Class A	5
Compatibility With Conventional Construction Materials	DIN 52 423	No signs of corrosion were observed on zinc, steel, galvanized steel, aluminum and copper no adverse effects with concrete, aerated concrete, brick, some natural stone, PVC, Plexiglass, and wood, for other materials consult Willseal

\*Attachment method of Willseal 600S was in a single joint compressed to 50% of original foam thickness. Joint material was constructed of calcium silicate board and is representative of field installation of the product.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

**NOTE: All Willseal Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.**

W600SDS/1222

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com  
800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | tremcocpg.com