

## ***Detailing the Rough Opening Comparing Your Options***

<b>Product</b>	<b>Dymonic 100</b>	<b>ExoAir 110</b>	<b>ExoAir 110AT</b>	<b>ExoAir 230 &amp; Mesh</b>
Permeance	Class III Vapor Retarder/Semi - Permeable	Class I Vapor Retarder/Impermeable	Class I Vapor Retarder/Impermeable	Permeable
High Solids	Yes	N/A	N/A	No
UV Exposure	No limit	30 Days	12 Months	12 Months
High Temperature Resistance	180°F (82°C)	158°F (70°C)	240°F (115°C)	240°F (115°C)
Cold Temperature Application	32°F (0°C) & Rising	40°F (5°C) & Rising	20°F (-6°C) & Rising	40°F (5°C) & Rising
NFPA 285 (Evaluated in an assembly)	Yes	No	Yes	Yes
Primer	Not Required	Required	Not Required	Not Required
Companion Products for Application	Dymonic 100 only	Dymonic 100 in the inside corners & to terminate the membrane; ExoAir Primer	Dymonic 100 in the inside corners and to terminate the membrane	Dymonic 100 in the inside corners and to fill voids; Tremco 2011 embedded in ExoAir 230
Packaging	10.1 oz cartridge 20 oz sausage	75' Rolls in widths of 6",9",12",18",24",36"	75' Rolls in widths of 4",6",9",12",18",24",36"	5 gal pail; 6" & 9" Rolls x 500'

12/18 MAT