SIMPLE SEALS OLUTION FOR LEAK-FREE BUILDINGS

Technologies

Simple Seal high-performance extrusions are designed to seal joints and gaps ranging from low to high movement conditions. For new construction and restoration projects, Simple Seal provides flexible, tear-resistant properties that will help to protect your building from air and moisture penetration.

Whether the need is for over an existing coating or under a new protective coating, Simple Seal offers a solution for that's right for your project.

Typical applications include window and door perimeters, EIFS joints, parapet walls, skylights, aluminum window seals, transition seals, curtain wall metal-to-metal joinery, sheet metal roof joints, penetrations, and many other gap and joint conditions.

Features & Benefits

- Ease of installation reduces time and labor costs
- Superior flexibility and movement capability
- Excellent tear resistance
- Wide operational temperature range
- Non-corrosive and corrosion resistant
- Available in a range of widths
- Custom designs with one or more notches

BEFORE







Product	Technology	Paintable	Left Exposed	Expansion Joints	Tear Resistance	Custom Notched	Door / Window Perimeter	Metal Joinery	Internal Glazing Seals	Under Coatings & Membranes	Warranty
Spectrem® Simple Seal Extruded Silicone Bridge	Silicone		X	X	X	X	X	X	Х	Х	20yr w/ Spec 1
Dymonic® Simple Seal Extruded Polyurethane Bridge	Urethane	Х	0-6 mos.	Х	Х	Х	Х			Х	10yr w/ Dym 100

Spectrem Simple Seal

STANDARD STOCK SIZES: 1", 1.5", 2", 3", 4", 6" (25, 38, 51, 76, 152 mm) [highlighted in chart below]

STANDARD STOCK COLORS: Black, White, Anodized Aluminum, Bronze, Aluminum Stone, Limestone, Sandstone [highlighted in chart below]

SPECIAL SIZES: Other sizes available include 2-1/2" (64 mm), 5" (127 mm) and 7 to 14" (178 to 355 mm) in 1" (25 mm) increments

SPECIAL COLORS: Adobe Tan, Buff, Champagne, Dark Bronze, Dusty Rose, Gray, Ivory, Light Bronze, Off White, Precast White, Rustic Brick

CUSTOM COLORS: Available upon request. Minimum order required.







WIDTH IN INCHES (MILLIMETERS)	STOCK SIZE	LEAD TIME	MIN ORDER QTY. IN FEET ((METERS)	SELLING UNIT OF MEASURE	FEET (METERS) / CASE	
1" (25)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
1.5" (38)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
2" (51)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
2.5 (64)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
3" (76)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
4" (102)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
5" (127)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
6" (152)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
7" (178)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
8" (203)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
9" (229)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
10" (254)	N0	3 WEEKS	250' (76.2)	1 ROLL	50 (15.2)	
11" (279)	N0	3 WEEKS	250' (76.2)	1 ROLL	50 (15.2)	
12" (305)	N0	3 WEEKS	250' (76.2)	1 ROLL	50 (15.2)	
13" (330)	N0	3 WEEKS	250' (76.2)	1 ROLL	50 (15.2)	
14" (355)	N0	3 WEEKS	250' (76.2)	1 ROLL	50 (15.2)	

Dymonic Simple Seal

STANDARD STOCK SIZES: 1.5", 2", 3", 4", 6" (38, 51, 76, 152 mm)

STANDARD STOCK COLORS: Light Gray

SPECIAL SIZES: 1", 2.5", 3.5", 4.5", 5", and 5.5" (25, 63.5, 88.9, 114.3, 127, and 139.7)



WIDTH IN INCHES (MILLIMETERS)	STOCK SIZE	LEAD TIME	MIN ORDER QTY. IN FEET (METERS)	SELLING UNIT OF MEASURE	FEET (METERS) / CASE	
1" (25)	NO	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
1.5" (38)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
2" (51)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
2.5" (63)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
3" (76)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
3.5" (89)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
4" (102)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	
4.5" (114)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
5" (127)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
5.5" (140)	N0	3 WEEKS	500' (152.4)	1 ROLL	100 (30.5)	
6" (152)	YES	4 DAYS	100' (30.5)	1 ROLL	100 (30.5)	