

1" MIN.

CROWN POURABLE SEALANT

VERIFY DEPTH WITH SEALANT MANUFACTURER

OPTIONAL: WEATHERPROOF SHEET-METAL RAIN COLLAR WITH SOLDERED/WELDED JOINTS OVERLAPPING PENETRATION POCKET WITH APPROPRIATE SEALANT (E.G., POLYURETHANE)

LIQUID APPLIED REINFORCED BASE COAT

LIQUID APPLIED TOP COAT

NONSHRINK GROUT

METAL PITCH PAN - CLEAN TO BRITTE METAL AND PRIME

LIQUID-APPLIED REINFORCED FLASHING—TURNED INTO PENETRATION POCKET

NOTES

1. PENETRATION POCKETS ARE NOT THE PREFERRED FLASHING METHOD AT PENETRATIONS BECAUSE THEY MAY BE A CONSTANT MAINTENANCE PROBLEM.
2. PRIMING OF THE SUBSTRATE MAY BE REQUIRED. FOLLOW SPECIFICATIONS AND MANUFACTURER'S RECOMMENDATIONS.



SHEET TITLE:
MEMBRANE-COATED PENETRATION
POCKET - SINGLE PENETRATION FULLY
REINFORCED OVER CONCRETE

SCALE:
NTS

DRAWING No.:
DWG NO. LA-CFR-20